



Garages Terraces Decorative Epoxy Resin Floor Coating With Multi Color Flakes

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Dignified Reputation: Blue Flake Epoxy Floor
- True To Form: High Gloss Urethane Finish Coat
- Materials: Epoxy Resin And Hardener
- Key Words: Interior Or Exterior Use
- Application: Wood, Brick, Ceramic, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: Garages Terraces Epoxy Resin Floor Coating, Multi Color Epoxy Resin Floor Coating



More Images



Product Description

Garages Terraces Decorative Epoxy Floor Coating With Multi Color Flakes

Quick Details Of Decorative Epoxy Floor Coating:

Our flake flooring system is very suitable for garages, parking lots, terraces, outdoor restaurants, indoor and outdoor environments. They also look great in retail locations because you need a wear-resistant, easy to clean, and non slip floor to leave a deep impression. The epoxy flake system uses decorative flakes to visually alter the appearance of concrete through strict application methods. They are the perfect solution to illuminate any new or old concrete floor. We use epoxy resin, polyurea, and polyaspartic in the coating system. The type of epoxy coating used depends on the space, purpose, and scope of the project.

Features Of Decorative Epoxy Floor Coating:

1. Solvent free, low maintenance
2. Impact resistant, self leveling
3. Odorless, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant

Advantages Of Decorative Epoxy Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Decorative Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

