Vinyl Flakes Waterproof Epoxy Resin Floor Coating With Gloss Matte Urethane Topcoat

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Official Term: Epoxy Waterproofing Flake Coating
 In Character: Broadcast Decorative Flake System

Materials: Epoxy Resin And HardenerKey Words: Interior Or Exterior Use

Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

• Highlight: Waterproof Epoxy Resin Floor Coating,

Vinyl Flakes Epoxy Resin Floor Coating, Gloss Matte Epoxy Resin Floor Coating



CREKOAT

More Images







Product Description

Vinyl Flakes Waterproof Epoxy Floor Coating With Gloss Matte Urethane Topcoat

Quick Details Of Waterproof Epoxy Floor Coating:

100% solid self-leveling epoxy resin is a versatile 100% solid, two component, high build epoxy floor coating designed specifically for applications that require heavy-duty protection. This is a 3-gallon kit that can easily cover 450 square feet. This 100% solid epoxy resin is very easy to use, has self-leveling properties, and provides a high gloss chemical corrosion resistant surface. Mix with Solid Colors pigment and sprinkle 1-3 pounds of vinyl flakes into epoxy resin for every 100 square feet of concrete floor. 100% solid self-leveling epoxy resin will provide a solid foundation for your topcoat. Seal your system with our industrial strength urethane topcoat.

Features Of Waterproof Epoxy Floor Coating:

- 1. Decorative and chemical resistant
- 2. Perfect for residential and commercial applications
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Waterproof Epoxy Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Waterproof Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China