Carbon Fiber Clear Epoxy Resin Penetrate Seal Coat Self Leveling UV Resistant

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
 Model Number: CK-ART1001
 Minimum Order Quantity: 400KG

• Price: US\$4.5-7.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Tag: Clear Penetrating Epoxy Sealer
 Particular: UV Resistant Casting Resin
 Key Words: Self Leveling, Self Degassing

Materials: High Glossy Epoxy Resin

Mixing Ratio: 1:1 By Volume

• Application: Casting, Coating And Art

Pot Life: 40 MinutesShelf Life: 12 Months

Highlight: Carbon Fiber Clear Epoxy Resin,
 Clear Epoxy Resin UV Resistant



More Images







Product Description

Carbon Fiber Clear Epoxy Resin Penetrate Seal Coat Self Leveling

Quick Details Of Clear Epoxy Resin:

Crystal clear epoxy resin is very suitable for showcasing natural wood veneer lamination and coating applications, such as wooden canoes and kayaks. The Crekoat crystal clear epoxy resin kit is the clearest choice for making solid wood look great or showcasing the cool elements of carbon fiber. For coating applications, this crystal clear formula will flow out and self leveling to penetrate and seal the wood, which helps prevent decay and fine cracks in the grains (also known as inspection). For laminations, it can easily wet glass fiber and carbon fiber fabrics. It solidifies into a high-strength, moisture-resistant, and particularly transparent solid, which can be completed with varnish or transparent topcoat.

Features Of Clear Epoxy Resin:

- 1. No bubbles and dries crystal clear
- 2. Fast-curing formulation
- 3. Free of solvents, VOC/BPA free
- 4. Resistant to yellowing from UV
- 5. Durable, water-clear, high-gloss
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling, self degassing product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This clear epoxy resin product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa·s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China