

Carbon Fiber Clear Epoxy Resin For Wood Metal Stone Low Viscosity

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
Model Number: CK-ART1001
Minimum Order Quantity: 400KG

• Price: US\$4.5-7.5/Kg

• Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Brand: Casting Epoxy Resin

Remarkable: Non-Blushing Marine Epoxy
Materials: Crystal Clear Epoxy Resin
Key Words: Self Leveling, Self Degassing

Mixing Ratio: 1:1 By Volume

• Application: Casting, Coating And Art

Pot Life: 40 MinutesShelf Life: 12 Months

Highlight: Low Viscosity Clear Epoxy Resin,
Carbon Fiber Clear Epoxy Resin



Product Description

Carbon Fiber Clear Epoxy Resin For Wood Metal Stone Low Viscosity

Quick Details Of Clear Epoxy Resin:

Our latest ultra clear resin system, designed by our research and development laboratory, specifically addresses the issues of absolute crystal clarity and resistance to sunlight yellowing, while showcasing high mechanical properties suitable for the manufacturing of structural composite materials. We use our resin formula with the lowest viscosity, suitable for adding fillers and powders. It is also suitable for many bonding and impregnation applications, where its low viscosity produces excellent wettability and resin saturation. Suitable for the manufacturing of universal composite materials for wood, metal, stone, and pottery products, as well as for the manufacturing of fabrics using glass fiber, carbon fiber, aramid, and other composite materials.

Features Of Clear Epoxy Resin:

- 1. Self-leveling ideal for laminating and coating
- 2. Creates a strong filleting or adhesive
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa·s	600-800 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China