



Flexible Clear Epoxy Resin Soft Two Component Casting Resin For Labels Doming

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: SGS, TDS, MSDS
- Model Number: CK-ART1001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-7.5/Kg
- Packaging Details: Bottle/Carton/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Identify: Clear Epoxy Glue
- Outstanding: Doming Resin
- Materials: Crystal Clear Epoxy Resin
- Key Words: Self Leveling, Self Degassing
- Mixing Ratio: 1:1 By Volume
- Application: Casting, Coating And Art
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: Flexible Clear Epoxy Resin,
Two Component Clear Epoxy Resin



Product Description

Flexible Clear Epoxy Resin Soft Two Component Casting Resin For Labes Doming

Quick Details Of Clear Epoxy Resin:

This epoxy resin remains flexible after curing. It is a two component clear epoxy casting resin. Very suitable for casting flexible objects. The addition of ultraviolet blocking agents to this epoxy resin ensures that it remains beautiful and transparent for a long period of time. Epoxy resin is a strong adhesive material. Therefore, this epoxy resin can also be used as a flexible adhesive between many surfaces and various types of materials. When handling this material, be sure to use safety gloves and goggles. Add components A and B in the correct proportion and mix thoroughly.

Features Of Clear Epoxy Resin:

1. UV Resistant, Self-leveling
2. No bubbles up to 5mm thick layer
3. Free of solvents, VOC/BPA free
4. Highest UV protection, anti yellowing
5. Durable, water-clear, high-gloss finish
6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	1800-2200 mPa·s	600-800 mPa·s
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C 24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards, Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China