

Transparent Coating Clear Epoxy Resin For Bar Tops Floors Counters Artworks

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
 Model Number: CK-ART1001
 Minimum Order Quantity: 400KG

• Price: US\$4.5-7.5/Kg

• Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Classify: Clear Epoxy For Countertops
 Significant: Clear Coating Epoxy Resins
 Materials: Crystal Clear Epoxy Resin
 Key Words: Self Leveling, Self Degassing

Mixing Ratio: 1:1 By Volume

• Application: Casting, Coating And Art

Pot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Transparent Coating Clear Epoxy Resin,

Bar Tops Clear Epoxy Resin



Product Description

Clear Epoxy Resin Transparent Coating For Bar Tops Floors Counters Artworks

Quick Details Of Clear Epoxy Resin:

This clear epoxy resin is very suitable for reproducing water surfaces in scale models or railway stereomodels. Mix the resin and hardener in a 1:1 ratio, apply, and wait for 24 hours for them to fully cure. It can also be poured into molds to form candy replicas such as jelly, candy, and juice. In addition, it can also be conveniently used to make transparent accessories, such as pendants or brooches. Resins can also be mixed with pigments to obtain more creative possibilities. Our transparent coating epoxy resin series - suitable for coating bar tops, floors, counters, artworks, and photos. High gloss, water transparent, super tough, self leveling and self degassing.

Features Of Clear Epoxy Resin:

- 1. Self-leveling & de-foaming resin
- 2. Unlimited number of casting layers
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa⋅s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China