

Crystal Clear Epoxy Resin Topcoat High Viscosity Fast Curing For Crafts

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
Model Number: CK-ART1001
Minimum Order Quantity: 400KG

• Price: US\$4.5-7.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Appellation: Clear Casting Epoxy
Great: High Gloss Appearance
Materials: Crystal Clear Epoxy Resin
Key Words: Self Leveling, Self Degassing

Mixing Ratio: 1:1 By Volume

• Application: Casting, Coating And Art

Pot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Crystal Clear Epoxy Resin,

High Viscosity Clear Epoxy Resin, Fast Curing Clear Epoxy Resin



Product Description

Clear Epoxy Resin Topcoat High Viscosity Fast Curing Resin For Crafts

Quick Details Of Clear Epoxy Resin:

Super fast curing resin - suitable for small crafts and any project topcoat. This transparent epoxy resin provides you with strong grip and high viscosity, no odor, and a curing time of 8-10 hours to meet your design and artistic needs. Heat resistant epoxy resin - Once fully cured, our crystal clear epoxy resin can resist scratches and high temperatures up to 100 ° C. This resin is the ideal topcoat for coasters or any items that come into contact with heated objects, with a 1:1 rapid curing epoxy resin (10 hour curing time.

Features Of Clear Epoxy Resin:

- 1. Excellent penetrating characteristic
- 2. No amine blush
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	1800-2200 mPa·s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China