

UV Resistant Clear Epoxy Resin Dry Seamless Without Yellowing

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
Model Number: CK-ART1001
Minimum Order Quantity: 400KG

• Price: US\$4.5-7.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

• Tab: Penetrating Epoxy Wood Sealer

Distinguished: Clear Gloss Coating
Materials: Crystal Clear Epoxy Resin
Key Words: Self Leveling, Self Degassing

Mixing Ratio: 1:1 By Volume

• Application: Casting, Coating And Art

Pot Life: 40 MinutesShelf Life: 12 Months

Highlight: UV Resistant Clear Epoxy Resin,
Dry Seamless Clear Epoxy Resin

CREKOAT



Product Description

UV Resistant Clear Epoxy Resin Dry Seamless Without Yellowing

Quick Details Of Clear Epoxy Resin:

Consistent curing time, this professional grade high viscosity epoxy resin can dry seamless without yellowing, discoloration, or bubbles. In fact, based on an ambient temperature of 23-25 degrees Celsius, it can cure within 10 to 12 hours. The higher the temperature, the faster the curing time. 100% non yellow, UV resistant finish Designed specifically for beginners and professional art projects, our epoxy resin cured products are crystal clear and have strong UV resistance, waterproof, and scratch resistant surface coverage capabilities. It is alicyclic or "non blushing", which means there is no oil film or amine "powder blusher" on it.

Features Of Clear Epoxy Resin:

- 1. Bonding wood, metal, and concrete
- 2. Pouring countertops, tabletops and bar tops
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa⋅s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China