

Casting Clear Epoxy Resin Glue For Tabletops Bar Surfaces Wood Finishes

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
 Model Number: CK-ART1001
 Minimum Order Quantity: 400KG

• Price: US\$4.5-7.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Brand Name: Deep Cast Epoxy Resin
 Characteristic: No Volatile Solvents
 Materials: Crystal Clear Epoxy Resin
 Key Words: Self Leveling, Self Degassing

Mixing Ratio: 1:1 By Volume

• Application: Casting, Coating And Art

Pot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Casting Clear Epoxy Resin,
Clear Epoxy Resin Glue

CREKOAT



Product Description

Casting Clear Epoxy Resin Glue For Tabletops Bar Surfaces Wood Finishes

Quick Details Of Clear Epoxy Resin:

The best part of casting epoxy resin with a transparent glossy coating is that it is hard and dry like rock, but provides a transparent finish that can enhance color or texture, thereby optimizing artistic style. Durable elasticity, our casting epoxy resin is also stronger and more elastic than standard glue, which means it can be used for tabletops, bar surfaces, wood finishes, or sealing packaging. This multifunctional epoxy resin is also used for pebble laying and floor coating. Some car enthusiasts also use our epoxy resin laminated carbon fiber components, including engine hoods, instrument panels, etc. It does not contain volatile organic compounds and is relatively insensitive to moisture.

Features Of Clear Epoxy Resin:

- 1. Extremely low viscosity, water white
- 2. Brilliantly clear, very tough finish
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa⋅s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China