

## Penetrating Clear Epoxy Resin Topcoat Sealer For Fiberglass Wooden Boats

Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: SGS, TDS, MSDS
- Model Number: CK-ART1001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-7.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



### Product Specification

- Trade Name: Epoxy Clear Coat
- Important: Penetrate Deep Into Wood
- Materials: Crystal Clear Epoxy Resin
- Key Words: Self Leveling, Self Degassing
- Mixing Ratio: 1:1 By Volume
- Application: Casting, Coating And Art
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Penetrating Clear Epoxy Resin,  
Clear Epoxy Resin Topcoat Sealer**



## Product Description

### Penetrating Clear Epoxy Resin Topcoat Sealer For Fiberglass Wooden Boats

#### Quick Details Of Clear Epoxy Resin:

Transparent coating is a water white penetrating epoxy resin with extremely low viscosity. The transparent coating can be cured into a bright, transparent and tough surface without the common "amine powder blusher" related to some epoxy resin films. The transparent coating does not contain solvents. Use transparent coated epoxy resin as coating and laminating resin for ship and woodworking applications. Transparent coatings can be used for various paint and topcoat options. From sealed wood to fiberglass wooden boats, the third system improves the waterproof protection of wood.

#### Features Of Clear Epoxy Resin:

1. Seal with clear coating and top
2. UV-protective coating
3. Free of solvents, VOC/BPA free
4. Highest UV protection, anti yellowing
5. Durable, water-clear, high-gloss finish
6. Useable on wood, concrete, glass

#### Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

#### Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	1800-2200 mPa·s	600-800 mPa·s
Density, g/cm <sup>3</sup>	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C 24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards, Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China