

Non Toxic Liquid Casting Resin Ultra Clear For Art Coating

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 4
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/
- Supply Ability:
- SGS, TDS, MSDS CK-ART1001 400KG US\$4.5-7.5/Kg Bottle/Carton/Wooden Box
- 3-7 Working days

CHINA

CREKOAT

- T/T, Western Union, MoneyGram
- ility: 1000000 Ton/Year

CREKOAT



Product Specification

- Sort:
- Excellent:
- Materials:
- Key Words:
- Mixing Ratio:
- Application:
- Pot Life:
- Shelf Life:
- Highlight:

Ultra Clear Epoxy Resin Safe For Home Use

- Crystal Clear Epoxy Resin
- Self Leveling, Self Degassing
- 1:1 By Volume
- Casting, Coating And Art
- 40 Minutes
- 12 Months
 - Non Toxic Liquid Casting Resin, Liquid Casting Resin Ultra Clear

CREKOAT



Our Product Introduction

Product Description

Non-Toxic Casting Resin For Art Coating And Casting Needs

Quick Details Of Casting Resin:

Non toxic two in one ratio epoxy resin. It is our safest and most widely used resin that can meet all your coating and casting needs. Odorless and free of bisphenol A, it is the most non-toxic resin in our home, and it is the resin used in all of our basic workshops. It is an optically transparent hybrid polymer resin with excellent UV stability. This universal resin has a medium viscosity and is suitable for art coatings and shallow casting. This resin is certified by ASTM as non-toxic, solvent-free, bisphenol A free, and odorless. It can be safely used at home when used according to instructions. Once fully cured, it can also be used as a food safety coating.

Features Of Casting Resin:

- 1. Water and chemical resistant
- 2. Solvent-free, nonyl phenol free
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Casting Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Casting Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa·s	600-800 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25ºC	
Curing Time	10-15hrs@25ºC, 6-8hrs@35ºC	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	





No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China