

Self Degassing Clear Casting Resin With Dyes Pigments Glitter Powder

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: SGS, TDS, MSDS
- Model Number: CK-ART1001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-7.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Tagging: Deep Pour Epoxy
- Momentous: UV Resistance
- Materials: Crystal Clear Epoxy Resin
- Key Words: Self Leveling, Self Degassing
- Mixing Ratio: 1:1 By Volume
- Application: Casting, Coating And Art
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Self Degassing Clear Casting Resin,
Clear Casting Resin With Dyes Pigments**



Product Description

Clear Casting Resin With Resin Dyes Pigments And Glitter Powder

Quick Details Of Casting Resin:

To mix correctly, each component should be thoroughly stirred together using a wooden stick or spoon. Avoid shaking the mixture to prevent the formation of persistent bubbles. The duration of processing epoxy resin after mixing is called processing time. It varies according to the amount of mixed epoxy resin. The larger the dosage, the shorter the processing time, usually lasting for 20 to 60 minutes. A warm environment will accelerate reactions and reduce working hours, while a cold environment will prolong reaction time. Resin dyes can be added to the mixture or various fillers, including pigments and glitter powder.

Features Of Casting Resin:

1. Low-odor 2-component epoxy resin
2. Resin viscosity: medium
3. Free of solvents, VOC/BPA free
4. Highest UV protection, anti yellowing
5. Durable, water-clear, high-gloss finish
6. Useable on wood, concrete, glass

Advantages Of Casting Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Casting Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	1800-2200 mPa·s	600-800 mPa·s
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C 24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards, Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China