

CHINA

CREKOAT

CK-ART1001

US\$4.5-7.5/Kg

1000000 Ton/Year

Bottle/Carton/Wooden Box

SGS, TDS, MSDS

1 Gallon Clear Casting Resin Kit Marine Grade Epoxy Resin For **Tabletop**

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 400KG
- Price:
- Packaging Details:
- Delivery Time:
- 3-7 Working days • Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability:

CREKOAT



Product Specification

- Type:
- First-Class:
- Materials:
- . Key Words:
- Mixing Ratio:
- Application:
- Pot Life:
- Shelf Life:
- Highlight:

Crystal Clear Epoxy Resin And Hardener Best Top Coat For Epoxy Resin

Crystal Clear Epoxy Resin

- Self Leveling, Self Degassing
- 1:1 By Volume
- Casting, Coating And Art
- 40 Minutes
- 12 Months
 - 1 Gallon Clear Casting Resin Kit, Marine Grade Clear Casting Resin Kit

CREKOAT



More Images



Our Product Introduction

1 Gallon Clear Casting Resin Kit Marine Grade Epoxy Resin For Tabletop

Quick Details Of Casting Resin:

Using this kit, you will receive half a gallon of tabletop epoxy resin and half a gallon of hardener. Once you mix them together, you have a whole gallon of water to use. The curing agent does not contain volatile organic compounds or solvent additives. This means that it is a non hazardous material, marine grade epoxy resin. To mix (if using the entire kit), simply mix the bottle without measuring. Mixing one gallon will cover approximately 37 square meters. Finally, it is approximately one eighth of an inch thick. If you want the coating to be thicker, you need to apply another layer.

Features Of Casting Resin:

- 1. Exhibits the highest strength
- 2. Resistant to dirt, grease and oil
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Casting Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Casting Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa·s	600-800 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25ºC, 6-8hrs@35ºC	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	





No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China