High Gloss Liquid Casting Resin Sealing Paint Surfaces Encapsulate And Artworks

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
Model Number: CK-ART1001
Minimum Order Quantity: 400KG

• Price: US\$4.5-7.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Description: Self Leveling Bar Top Epoxy

• Superb: Chemical Resistant

Materials: Crystal Clear Epoxy ResinKey Words: Self Leveling, Self Degassing

Mixing Ratio: 1:1 By Volume

• Application: Casting, Coating And Art

Pot Life: 40 MinutesShelf Life: 12 Months

High Gloss Liquid Casting Resin,

Chemical Resistant Liquid Casting Resin



Product Description

High Gloss Casting Resin Sealing Paint Surfaces Encapsulate And Artworks

Quick Details Of Casting Resin:

In fact, casting resin will continue and remain clear, which will enable you to apply it to all types of projects. casting resin can be used to paint surfaces, encapsulate, and all other artworks you are creating. No matter what you are doing, it will be sealed in a waterproof barrier, able to resist impact or surface damage. Because it is self leveling, you never have to worry about it being thicker in some areas and too thin in others. You will never see any craters, fish eyes, or crawls. It will not lose its integrity on sharp corners or edges. When you use it, any area it covers will have a high gloss surface.

Features Of Casting Resin:

- 1. Clear epoxy coating of medium viscosity
- 2. Durable design and long lasting
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Casting Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Casting Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa·s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China