UV Resistant Liquid Casting Resin Coating For Tabletop Artworks

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
 Model Number: CK-ART1001
 Minimum Order Quantity: 400KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

• Logotype: Clear Resin For Table Top

First-Rate: UV Resistant Epoxy

Materials: Crystal Clear Epoxy ResinKey Words: Self Leveling, Self Degassing

Mixing Ratio: 1:1 By Volume

• Application: Casting, Coating And Art

Pot Life: 40 MinutesShelf Life: 12 Months

Highlight: MSDS Liquid Casting Resin,
 UV Resistant Liquid Casting Resin



More Images





Product Description

UV Resistant Liquid Casting Resin Coating For Tabletop Artworks

Quick Details Of Casting Resin:

Our tabletop epoxy resin provides outstanding UV resistance, ensuring your artwork remains unaffected by yellowing caused by sunlight or UV rays. While it's highly resistant, direct sunlight exposure should be avoided to maintain its original appearance. With a swift curing process and excellent air release properties, this resin enhances the surface quality of all projects. For those seeking an even smoother finish with fewer bubbles, employing mild heat at 160 degrees Fahrenheit can expedite curing and minimize surface imperfections. Experience superior UV protection and impeccable surface quality with our tabletop epoxy resin.

Features Of Casting Resin:

- 1. Remarkable UV resistance, safeguarding your artwork from yellowing
- 2. Its rapid curing and air-release properties contribute to a flawless finish
- 3. Achieving a smoother and more professional result in your projects
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Casting Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Casting Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa·s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China