

## Thick Liquid Casting Resin Transparent Durable Glossy Top Coating

Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: SGS, TDS, MSDS
- Model Number: CK-ART1001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-7.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



### Product Specification

- Heading: Clear Coat For Countertops
- Outstanding: Low VOCs, Solvent Free
- Materials: Crystal Clear Epoxy Resin
- Key Words: Self Leveling, Self Degassing
- Mixing Ratio: 1:1 By Volume
- Application: Casting, Coating And Art
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Thick Liquid Casting Resin,  
Glossy Top Liquid Casting Resin**



## Product Description

### Thick Liquid Casting Resin Transparent Durable Glossy Top Coating

#### Quick Details Of Casting Resin:

Casting Resin is a versatile liquid plastic coating that can self level and then harden to form a thick, transparent, durable, and glossy surface. This product needs to be mixed with an equal amount of resin and curing agent in the measuring container. Quick shaping with a hard surface. The kit contains an equal amount of resin and hardener Kraftkote has a shelf life of one year. We recommend placing it in its original container and keeping it away from sunlight. The temperature is between 70 and 80 degrees, and the humidity is less than 50%. We suggest that the pouring thickness should not exceed 1/8 ". To obtain a thicker finish, please repeat this process after the previous layer has cured for at least 24 hours.

#### Features Of Casting Resin:

1. 100% solids, water clear
2. High build application
3. Free of solvents, VOC/BPA free
4. Highest UV protection, anti yellowing
5. Durable, water-clear, high-gloss finish
6. Useable on wood, concrete, glass

#### Advantages Of Casting Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

#### Product Descriptions Of Casting Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	1800-2200 mPa·s	600-800 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	10-15hrs@25°C, 6-8hrs@35°C 24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards, Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China