

Self Priming Liquid Glass Casting Resin For Art Acrylic Casting Domino Labels TDS

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: SGS, TDS, MSDS
- Model Number: CK-ART1001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-7.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Tags: Clear Resin And Hardener
- Marvelous: Self Priming, High Viscosity
- Materials: Crystal Clear Epoxy Resin
- Key Words: Self Leveling, Self Degassing
- Mixing Ratio: 1:1 By Volume
- Application: Casting, Coating And Art
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: Self Priming Liquid Glass Casting Resin, TDS Liquid Glass Casting Resin



Product Description

Liquid Glass Casting Resin For Art Acrylic Casting Domino Labels

Quick Details Of Casting Resin:

Epoxy liquid glass epoxy is a two part ultra clear epoxy coating resin for professional artists and enthusiasts to use. Epoxy glass epoxy is easy to use with a 1:1 mix ratio. This transparent epoxy resin is designed for coating almost anything, such as resin art, acrylic casting, domino labels and magnets, mosaics, photos, polymer clay jewelry, etc. We suggest conducting a test before using epoxy glass on your precious items to ensure that you are satisfied with the results. Epoxy glass epoxy can produce a high gloss, glass like surface. Epoxy glass can be easily colored with opaque pigments and semi transparent dyes. You can also use our beautiful metallic powder series, glitter powder, or pearl series.

Features Of Casting Resin:

1. Highly transparent crystal clear
2. Excellent self -ventilation
3. Free of solvents, VOC/BPA free
4. Highest UV protection, anti yellowing
5. Durable, water-clear, high-gloss finish
6. Useable on wood, concrete, glass

Advantages Of Casting Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Casting Resin:

| Item | Epoxy Resin(A) | Hardener(B) |
|----------------------------|---|---------------|
| Appearance | Liquid | Liquid |
| Color | Transparent | Transparent |
| Viscosity@25°C | 1800-2200 mPa·s | 600-800 mPa·s |
| Density, g/cm ³ | 1.07±0.05 | 0.95±0.03 |
| Mix Ratio | 1:1 by volume | |
| Hardness | Shore, D85-90 | |
| Pot Life | 40-50mins@25°C | |
| Curing Time | 10-15hrs@25°C, 6-8hrs@35°C 24hrs, Dry Completely | |
| Max Pour Depth | 1-8cm max per single pour | |
| Shelf Life | 12 Months | |
| Application | Ideal for all Casting, Coating and Art Projects including Cutting Boards, Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and Acrylic Pour Paintings, Geode Paintings, Molds, River Tables | |





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China