

Commercial Epoxy Flake Floor Coating In Office Retail Store Garage

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Merchandise Branding: Concrete Epoxy Paint With Flakes
- Key Element: Brilliant Longevity
- Key Words: Interior And Exterior Use
- Materials: Epoxy Resin And Hardener
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Commercial Epoxy Flake Floor Coating, Office Epoxy Flake Floor Coating**



Product Description

Commercial Epoxy Flake Floor Coating Used In Offices Retail Stores Garages

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake coating is a flooring solution that combines epoxy resins and decorative flakes. With exceptional durability, chemical resistance, and impact resistance, it is widely used in commercial and residential spaces. The epoxy resin acts as a strong adhesive, binding the decorative flakes to create a seamless and visually appealing finish. It finds applications in offices, retail stores, garages, and industrial facilities, where its customizable design options and easy maintenance make it an ideal choice. Epoxy flake coating offers both functional and aesthetic benefits, providing a durable and attractive flooring solution for various environments.

Features Of Epoxy Flake Floor Coating:

1. Offers reliable surface protection
2. Decorative: Adds aesthetic appeal
3. Odorless, low VOC, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150 mPa.s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China