

Slip Resistance Epoxy Flake Floor Coating For Showrooms Garages

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Trade Item Designation: Blue Epoxy Flakes
- Defining Characteristic: Impact Resistant
- Key Words: Interior And Exterior Use
- Materials: Epoxy Resin And Hardener
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: Slip Resistance Epoxy Flake Floor Coating, Garage Epoxy Flake Floor Coating



Product Description

Slip Resistance Epoxy Flake Floor Coating For Warehouses Showrooms Garages

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake coating is a type of flooring system composed of epoxy resin and decorative colored flakes. It offers a durable, seamless, and attractive finish that is resistant to abrasion, chemicals, and moisture. The flakes add texture and depth to the coating, creating a unique and customizable design. Epoxy flake coating is commonly used in commercial and industrial settings such as warehouses, showrooms, and garages. It is also suitable for residential applications such as basements and kitchens. This coating system is easy to clean and maintain, making it a popular choice for high-traffic areas. Additionally, it provides excellent slip resistance, improving safety in the workplace or home.

Features Of Epoxy Flake Floor Coating:

1. Enhances safety by preventing slips and falls
2. Smooth surface without joints or seams
3. Odorless, low VOC, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150 mPa·s
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China