

Fast Curing Epoxy Flake Floor Coating For Commercial Warehouses Garages

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Item Naming: Floor Paint Sprinkles
 Factor: Seamless Application
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

 Highlight: Fast Curing Epoxy Flake Floor Coating, Warehouses Epoxy Flake Floor Coating



Product Description

Fast Curing Epoxy Flake Floor Coating For Commercial Warehouses Garages

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake coating stands as an innovative flooring solution that redefines both functionality and aesthetics. Blending epoxy resin with decorative flakes, it creates a multi-dimensional, textured surface that captivates the senses. This coating goes beyond conventional options with its exceptional durability, offering long-lasting protection against heavy impacts, abrasions, and even harsh chemicals. Its versatile nature makes it an ideal choice for diverse environments, ranging from residential homes to commercial spaces like retail stores and offices. The customizable color combinations and patterns of epoxy flake coating add a touch of personalization, transforming any space into a visually stunning masterpiece.

Features Of Epoxy Flake Floor Coating:

- 1. Fast curing reducing downtime
- 2. Ideal for commercial spaces
- 3. Odorless, low VOC, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China