

Blend Chips Epoxy Flake Floor Coating For Garage Concrete Flooring

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

• Trade Marking: Full Flake Epoxy Garage Floor

Component: Glossy Appearance
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

• Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Blend Chips Epoxy Flake Floor Coating,

Garage Epoxy Flake Floor Coating



Product Description

Blend Chips Epoxy Flake Floor Coating Solution For Concrete Flooring

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake coating revolutionizes the flooring landscape, marrying strength with artistic finesse. The fusion of epoxy resin and decorative flakes crafts a mesmerizing three-dimensional effect, transforming ordinary floors into captivating artistic expressions. Its seamless installation guarantees a crack-resistant, stain-repellent surface, perfect for bustling environments, requiring minimal upkeep.

Offering a plethora of color options and design flexibility, epoxy flake coating becomes a canvas for boundless creativity, allowing individuals to personalize floors to mirror their unique style. Seamlessly intertwining durability, aesthetics, and customizable design, this coating delivers an unparalleled flooring experience, standing out as an extraordinary choice in the market.

Features Of Epoxy Flake Floor Coating:

- 1. Commercial spaces, warehouses, garages
- 2. Solution for long-term floor protection
- 3. Odorless, low VOC, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China