

# MSDS Epoxy Flake Floor Coating Scratches Resistant Easy To Clean

## **Basic Information**

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 1000000 Ton/Year



# **Product Specification**

Merchandise Designation: Grey Flake Epoxy Floor
 Detail: Low Maintenance
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: MSDS Epoxy Flake Floor Coating,

**Epoxy Flake Floor Coating Scratches Resistant** 



## **Product Description**

#### Non-Slip Epoxy Flake Floor Coating Scratches Resistant Easy To Clean

#### **Quick Details Of Epoxy Flake Floor Coating:**

Epoxy flake coating combine epoxy resin with decorative flakes, it creates a stunning, multi-dimensional surface that transforms any space into a visual masterpiece. This remarkable coating excels in durability, offering exceptional resistance to heavy impacts, scratches, and chemicals. Its versatility extends beyond traditional applications, finding its place in luxury homes, art galleries, and trendy boutiques. The customizable color combinations and intricate patterns of epoxy flake coating provide endless possibilities for artistic expression. With its ability to seamlessly merge functionality and aesthetics, this coating sets a new standard in flooring, leaving a lasting impression that speaks volumes about innovation and sophistication.

#### Features Of Epoxy Flake Floor Coating:

- 1. Low VOC (Volatile Organic Compounds)
- 2. Non-slip texture, customizable designs
- 3. Odorless, low VOC, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

#### **Advantages Of Epoxy Flake Floor Coating:**

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

#### **Product Descriptions Of Epoxy Flake Floor Coating:**

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China