

Fast Curing Polyaspartic Floor Coating High UV Stability Low VOC

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-PLS1001
Minimum Order Quantity: 400KG

• Price: US\$10.5-16.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 1000000 Ton/Year



Product Specification

Product Identity: Epoxy Flake Floor System
 Attribute: Excellent Wear Resistance
 Key Words: Interior And Exterior Use
 Materials: 95% Solid Polyaspartic
 Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: Fast Curing Polyaspartic Floor Coating,
 Polyaspartic Floor Coating High UV Stability



Product Description

Fast-Curing Polyaspartic Floor Coating High UV Stability Low VOC

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic floor coating is a type of coating that consists of polyaspartic esters, which are derived from polyurea chemistry. It is known for its exceptional durability, chemical resistance, and fast curing time. This coating exhibits high UV stability and can withstand heavy traffic, making it ideal for industrial and commercial applications such as warehouses, automotive facilities, and manufacturing plants. Its rapid curing properties enable quick turnaround times, minimizing downtime during installation. Additionally, polyaspartic floor coating offers excellent adhesion to various substrates, including concrete, making it a versatile choice for a wide range of flooring projects.

Features Of Polyaspartic Floor Coating:

- 1. Provides long-lasting protection
- 2. It dries quickly, reducing downtime
- 3. Odorless, Low VOC, environmentally
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	200 cps	250 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D50-55	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China