

Non Slip Polyaspartic Floor Coating For Patios And Pool Decks

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-PLS1001
Minimum Order Quantity: 400KG

• Price: US\$10.5-16.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Trade Item Labeling: Full Broadcast Flake Floor
 Dimension: Decorative Versatility
 Key Words: Interior And Exterior Use
 Materials: 95% Solid Polyaspartic
 Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: Non Slip Polyaspartic Floor Coating,
 Pool Decks Polyaspartic Floor Coating



Product Description

Non-Slip Polyaspartic Floor Coating For Patios And Pool Decks

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic floor coating sets itself apart with its unique formulation and exceptional characteristics. Comprised of polyaspartic esters derived from polyurea chemistry, this coating offers a remarkable blend of durability, chemical resistance, and rapid curing. What distinguishes it further is its remarkable flexibility, allowing it to withstand temperature fluctuations without cracking or peeling. This makes it an ideal choice for outdoor applications, such as stadiums, patios, and pool decks. Its high gloss finish enhances the aesthetic appeal while providing excellent abrasion resistance. Whether in high-traffic areas or demanding industrial settings, polyaspartic floor coating ensures long-lasting performance and protection, making it a preferred option for a wide range of flooring needs.

Features Of Polyaspartic Floor Coating:

- 1. Slip-resistant, a safe and non-slip surface
- 2. Offers a shiny and aesthetically finish
- 3. Odorless, Low VOC, environmentally
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	200 cps	250 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D50-55	
Pot Life	30-40mins@25ºC	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China