

Low VOC Polyaspartic Floor Coating For Concrete Wood Surface

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-PLS1001
Minimum Order Quantity: 400KG

• Price: US\$10.5-16.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 1000000 Ton/Year



Product Specification

• Item Classification: Chips For Garage Floor

Character: Moisture Barrier

Key Words: Interior And Exterior Use Materials: 95% Solid Polyaspartic

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Low VOC Polyaspartic Floor Coating,

Polyaspartic Floor Coating For Concrete

Surface



Product Description

Low VOC Polyaspartic Floor Coating Applied On Concrete Wood Surface

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic floor coating stands out due to its versatility and eco-friendly nature. Composed of polyaspartic esters derived from polyurea chemistry, this coating offers a range of benefits. Its low VOC (volatile organic compound) content makes it environmentally friendly, while still delivering exceptional durability and chemical resistance. This coating's versatility shines through its ability to be applied on various surfaces, including concrete, wood, and even existing coatings. It is equally suitable for residential, commercial, and industrial settings, providing a seamless and visually appealing finish. With its fast cure time, minimal odor, and easy maintenance, polyaspartic floor coating offers a sustainable flooring solution that meets both aesthetic and environmental standards.

Features Of Polyaspartic Floor Coating:

- 1. Creates a smooth and seamless surface
- 2. Easy to clean, requires minimal maintenance
- 3. Odorless, Low VOC, environmentally
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	200 cps	250 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D50-55	
Pot Life	30-40mins@25ºC	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China