UV Resistance Polyaspartic Floor Coating Preventing Yellowing In Outdoor

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-PLS1001
Minimum Order Quantity: 400KG

• Price: US\$10.5-16.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Brand Signature: Flakes Floor Paint
Specialty: Seamless Integration
Key Words: Interior And Exterior Use
Materials: 95% Solid Polyaspartic
Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By Weight Pot Life: 40 Minutes

• Shelf Life: 12 Months

• Highlight: UV Resistance Polyaspartic Floor Coating,

Preventing Yellowing Polyaspartic Floor

Coating



Product Description

UV Resistance Polyaspartic Floor Coating Preventing Yellowing In Outdoor

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic floor coating sets itself apart with its exceptional UV resistance. Formulated with polyaspartic esters derived from polyurea chemistry, this coating exhibits high resistance to UV radiation, preventing yellowing, fading, or discoloration over time. It remains vibrant and maintains its original appearance, even in outdoor or sunlit environments. This makes it a perfect choice for spaces like outdoor patios, sports arenas, or retail storefronts. With its ability to withstand prolonged exposure to sunlight, polyaspartic floor coating offers long-lasting protection and preserves the aesthetic appeal of the flooring, ensuring a vibrant and visually appealing environment for years to come.

Features Of Polyaspartic Floor Coating:

- 1. Quick re-application, minimizing downtime
- 2. Resistance against wear and abrasion
- 3. Odorless, Low VOC, environmentally
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	200 cps	250 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D50-55	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China