

# **Color Flake Polyaspartic Floor Coating For High - Traffic Areas**

## **Basic Information**

. Place of Origin: **CHINA** . Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-PLS1001 • Minimum Order Quantity: 400KG

• Price: US\$10.5-16.5/Kg

 Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

. Supply Ability: 1000000 Ton/Year



# **Product Specification**

• Merchandise Identifier: Color Flake Epoxy Garage Floor

Trait: High Durability

. Key Words: Interior And Exterior Use 95% Solid Polyaspartic Materials: · Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By Weight Pot Life: 40 Minutes

Shelf Life: 12 Months

• Highlight: Color Flake Polyaspartic Floor Coating,

**High Traffic Areas Polyaspartic Floor Coating** 



CREKOAT



## **Product Description**

#### Color Flake Polyaspartic Floor Coating Ideal For High-Traffic Areas

#### **Quick Details Of Polyaspartic Floor Coating:**

Polyaspartic floor coating stands out for its remarkable scratch and abrasion resistance. Formulated with polyaspartic esters derived from polyurea chemistry, this coating forms a tough and resilient surface that can withstand heavy wear and tear. Whether it's a busy warehouse, high-traffic retail space, or industrial facility, this coating offers exceptional durability, protecting the underlying surface from scratches, scuffs, and marks caused by foot traffic or moving equipment. Its ability to maintain its pristine condition even under demanding conditions makes polyaspartic floor coating the ideal choice for areas that require long-lasting protection against abrasion, ensuring a clean and professional appearance that lasts.

#### Features Of Polyaspartic Floor Coating:

- 1. Ideal for high-traffic areas
- 2. Withstands extreme temperatures
- 3. Odorless, Low VOC, environmentally
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

#### **Advantages Of Polyaspartic Floor Coating:**

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

#### **Product Descriptions Of Polyaspartic Floor Coating:**

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	200 cps	250 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D50-55	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China