

Quick Polyaspartic Floor Coating Withstands Extreme Temperatures

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 400KG
- Price: US\$10.5-16.5/Kg
- Packaging Details: Bottle/Carton/Wooden Box
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Article Title: Garage Floor Paint And Flakes
- Property: Non-Yellowing Formula
- Key Words: Interior And Exterior Use
- Materials: 95% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Quick Polyaspartic Floor Coating, Garage Polyaspartic Floor Coating**



Product Description

Quick Application Polyaspartic Floor Coating Withstands Extreme Temperatures

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic floor coating distinguishes itself with its excellent chemical resistance. Comprised of polyaspartic esters derived from polyurea chemistry, this coating forms a robust barrier against a wide range of chemicals, including oils, solvents, acids, and alkalis. It withstands chemical spills and prevents corrosion or damage to the underlying surface, making it suitable for industrial facilities, laboratories, and automotive workshops. The superior chemical resistance of polyaspartic floor coating ensures long-term durability and maintains a clean and hygienic environment. With its ability to withstand harsh chemical exposures, this coating offers peace of mind and reliable protection in even the most demanding chemical-intensive settings.

Features Of Polyaspartic Floor Coating:

1. Suitable for both hot and cold environments
2. Resists stains, oils, chemicals, and food spills
3. Odorless, Low VOC, environmentally
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	200 cps	250 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D50-55	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China