

MSDS Seamless Installation Non Slip Epoxy Floor Coating Increases Traction And Grip

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-WZ3001
Minimum Order Quantity: 400KG

• Price: US\$3.5-5.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Merchandise Label: Anti Slip EpoxyHighlight: Heat Resistance

Key Words: Seamless, High Gloss Finish
 Materials: Epoxy Resin And Hardener
 Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 3:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: MSDS Non Slip Epoxy Floor Coating,
 Non Slip Epoxy Floor Coating Seamless

CREKOAT



Product Description

Seamless Installation Non Slip Epoxy Floor Coating Increases Traction And Grip

Quick Details Of Non Slip Epoxy Floor Coating:

Non-slip epoxy floor coating is a revolutionary solution that prioritizes safety and minimizes the risk of accidents caused by slippery surfaces. Unlike traditional anti-slip options, this coating goes beyond grip enhancement. It boasts remarkable resistance to extreme temperatures, heavy impacts, and chemical spills, making it an ideal choice for demanding environments. Whether in industrial settings, commercial spaces, or residential areas, non-slip epoxy floor coating stands out as a reliable and long-lasting solution. With its seamless installation, customizable design options, and low maintenance requirements, it not only ensures safety but also adds an aesthetically pleasing touch to any space.

Features Of Non Slip Epoxy Floor Coating:

- 1. Increases traction and grip on smooth or uneven floors
- 2. Suitable for outdoor spaces, walkways, and ramps
- 3. Seamless application: creates a smooth finish
- 4. Easy to apply, effortless to clean and maintain
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Non Slip Epoxy Floor Coating:

Epoxy floor coating is a flooring system composed of epoxy resin and hardener that creates a strong, durable, and long-lasting surface. This coating system is highly resistant to abrasion, chemicals, and moisture, making it ideal for high-traffic areas in commercial, industrial, and residential settings. Epoxy floor coating can be customized with a variety of colors, patterns, and textures, providing a unique and decorative finish. It is easy to clean and maintain, reducing the need for harsh chemicals and providing a low-maintenance flooring solution. Epoxy floor coating is also slip-resistant, improving safety in workplaces and homes. This flooring system can be applied to a variety of substrates, including concrete, wood, and metal, providing versatility and adaptability to any space.

Product Descriptions Of Non Slip Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Customized Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	3:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China