

Hygienic Epoxy Flake Floor Coating For Hospital Residential Garages Flooring

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-6.0/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Line Signature Label: Epoxy Flakes 50 Lb
- Singular Trait: Innovative 3D Effects
- Key Words: Interior And Exterior Use
- Materials: Epoxy With Flakes
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: Hygienic Epoxy Flake Floor Coating, Epoxy Flake Floor Coating For Hospital



Product Description

Hygienic Epoxy Flake Floor Coating For Hospital Residential Garages Flooring

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating reimagines flooring excellence. By fusing epoxy resin and decorative flakes, it crafts a floor that's not only enduring but also a visual masterpiece. The surface withstands heavy-duty demands, from traffic to spills, making it ideal for homes, showrooms, and more. Customization options abound, enabling personalized patterns and hues, turning every space into an expression of individuality. This isn't just a coating; it's a statement, an intersection of strength and artistry. Experience a floor that doesn't compromise on durability or aesthetics – it elevates both, creating a dynamic space that exudes sophistication and uniqueness.

Features Of Epoxy Flake Floor Coating:

1. Ideal for residential garages flooring
2. High reflectivity enhances space illumination
3. Hygienic for hospital healthcare facilities
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150 mPa.s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China