

Versatility Art Epoxy Flake Floor Coating Eco Friendly Retail Elegance

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.5-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Trade Item Identifier: Surecrete Epoxy Flakes
 Specialized Characteristic: Temperature Adaptable
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: Versatility Art Epoxy Flake Floor Coating,

Epoxy Flake Floor Coating Eco Friendly

CREKOAT



Product Description

Versatility Art Epoxy Flake Floor Coating Eco-Friendly Retail Elegance

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating stands as a testament to modern flooring ingenuity. The fusion of epoxy resin and decorative flakes produces not just a surface, but an experience. It thrives under pressure, resisting impacts and chemicals while maintaining its allure. Versatility is its hallmark, fitting seamlessly into homes, offices, and retail spaces. However, it's not just about function – the array of colors and flake designs turns the floor into an art form. This coating doesn't merely cover; it transforms, introducing a sense of elegance that's as robust as it is eye-catching. Welcome a new era of flooring, where strength meets creativity, and everyday spaces become showcases of both resilience and style.

Features Of Epoxy Flake Floor Coating:

- 1. Suitable for wet area damp environments
- 2. Eco-Friendly, low environmental impact
- 3. Retail elegance enhances store aesthetics
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China