

Unique Craft Epoxy Flake Floor Coating For Garages Shops Homes

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 400KG
- Price: US\$4.5-6.0/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Labelled Item Title: Seamless Flake Flooring
- Noteworthy Inclusion: Premium Solvent Resistance
- Key Words: Interior And Exterior Use
- Materials: Epoxy With Flakes
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Unique Craft Epoxy Flake Floor Coating, Epoxy Flake Floor Coating For Garages**



Product Description

Unique Craft Epoxy Flake Floor Coating For Garages Shops Homes

Quick Details Of Epoxy Flake Floor Coating:

Unveil a flooring marvel with Epoxy Flake Floor Coating. Melding epoxy resin and decorative flakes, it forges a floor that's a masterpiece of endurance and aesthetics. Designed to withstand heavy-duty challenges, from constant footfalls to chemical spills, it's an impeccable choice for garages, shops, and even upscale homes. The real magic lies in the creative freedom it offers – a kaleidoscope of colors and flake sizes lets you craft your unique floor narrative. Beyond being just functional, it's a canvas where durability and design coalesce, creating a visual symphony that resonates strength and elegance in perfect harmony.

Features Of Epoxy Flake Floor Coating:

1. Museums & Galleries Ideal for art spaces
2. Chemical resists corrosive substances
3. Speedy Installation, quick application
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150 mPa·s
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China