

Office Spaces Epoxy Flake Floor Coating Against Heavy Impacts And Chemical

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Trade Marking Schema: Rustoleum Floor Flakes
 Highlighting: Sealed Porosity Defense
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: Office Spaces Epoxy Flake Floor Coating,

Epoxy Flake Floor Coating Against Chemical



Product Description

Office Spaces Epoxy Flake Floor Coating Against Heavy Impacts And Chemical

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating introduces a new era of flooring sophistication. Blending epoxy resin with decorative flakes, it crafts a floor that's not only robust but an embodiment of artistry. Its endurance against heavy impacts and chemical challenges is matched only by its visual splendor. Be it residential spaces or commercial settings, this coating's adaptability shines through. The true allure, however, is its ability to transform spaces into personalized expressions. A spectrum of colors and flake designs invites creativity, turning floors into captivating canvases. It's not just about covering the ground; it's about elevating it into a realm where resilience marries aesthetics seamlessly.

Features Of Epoxy Flake Floor Coating:

- 1. Office spaces professional appearance
- 2. Temperature resilience withstands heat
- 3. Non-slip enhanced safety features
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China