

High Gloss Blending Color Epoxy Flake Floor Coating For Hangars Aircraft Facilities

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 1000000 Ton/Year



Product Specification

Product Nomination:
 Behr Decorative Color Flakes

Essential Trait: Multi-Layered Depth
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Blending Color Epoxy Flake Floor Coating,

High Gloss Epoxy Flake Floor Coating, Epoxy Flake Floor Coating For Hangars



Product Description

Blending Color Epoxy Flake Floor Coating For Hangars Aircraft Facilities

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating epitomizes flooring innovation. Blending epoxy resin with decorative flakes, it crafts a floor that's a fusion of strength and style. Withstanding the rigors of daily use, from foot traffic to spills, it finds its home in garages, homes, and commercial spaces. Yet, its allure doesn't stop at durability. A myriad of colors and flake combinations allows you to tailor your floor, transforming it into an artful centerpiece. This isn't just covering the ground; it's creating a symphony of functionality and aesthetics, where resilience dances with design. Embrace a new era of flooring that doesn't just withstand life – it enhances it, proving that a floor can be more than just a surface.

Features Of Epoxy Flake Floor Coating:

- 1. Sport facilities durable for athletic areas
- 2. Longevity provides enduring protection
- 3. Tough coating for aircraft hangars
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China