

Commercial Spaces Epoxy Flake Floor Coating Innovative Resistant To Water

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Commodity Designator: Parchem Flake Flooring

Defining Element: Customizable Texture Options
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: Commercial Epoxy Flake Floor Coating,
 Epoxy Flake Floor Coating Water Resistant

CREKOAT



Product Description

Commercial Spaces Epoxy Flake Floor Coating Innovative Resistant To Water

Quick Details Of Epoxy Flake Floor Coating:

Introducing Epoxy Flake Floor Coating, where strength meets artistry. This innovative blend of epoxy resin and decorative flakes redefines flooring. It stands up to the challenges of daily life, from heavy use to spills, making it a perfect fit for homes, commercial spaces, and more. Beyond its durability, it's a canvas for creativity. A spectrum of colors and flake designs lets you design a floor that's uniquely yours, turning spaces into living works of art. It's not just about protection; it's about infusing style and personality into every step. Experience a flooring solution that doesn't just endure life – it enhances it, creating an environment where toughness harmonizes with elegance.

Features Of Epoxy Flake Floor Coating:

- 1. Rust prevention against metal corrosion
- 2. Marine applications resistant to water
- 3. Suitable for data centers tech environments
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China