

Unique Epoxy Flake Floor Coating Customized Patterns Mica Flakes In Epoxy Sound Reduction Floor

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 400KG
- Price: US\$4.0-6.0/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Merchandise Identity: Deco Flake Flooring
- Outstanding Quality: Seamless Anti-Abrasion
- Key Words: Interior And Exterior Use
- Materials: Epoxy With Flakes
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Unique Epoxy Flake Floor Coating,
Epoxy Flake Floor Coating Customized Patterns**



Product Description

Unique Customized Patterns Mica Flakes In Epoxy Sound Reduction Floor

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating: a fusion of strength and aesthetics. The marriage of epoxy resin and decorative flakes births a floor that is both durable and visually captivating. Its robustness makes it a natural fit for garages, commercial spaces, and homes, easily resisting daily wear and tear. But this coating goes beyond practicality. With a palette of colors and flake patterns, it becomes a platform for creativity, allowing you to design floors that mirror your unique taste. It's more than protection; it's a statement. The combination of resilience and elegance transforms ordinary spaces into extraordinary ones.

Features Of Epoxy Flake Floor Coating:

1. One-of-a-Kind Designs
2. Adds charm to hotels and resorts
3. Helps dampen noise impact
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150 mPa.s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China