Commercial Areas Paint Chip Epoxy Floor Coating With Blending Decorative Flakes

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Article Appellative: Vinyl Chip Garage Floor
 Distinct Aspect: Heavy-Duty Protection
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

 Highlight: Commercial Areas Epoxy Floor Coating, Epoxy Floor Coating With Blending Flakes

CREKOAT



Product Description

Commercial Areas Paint Chip Epoxy Floor With Blending Decorative Flakes

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating reimagines flooring dynamics. Blending epoxy resin and decorative flakes, it creates an unparalleled fusion of strength and style. While its durability stands strong against daily demands, it's the artistic dimension that truly sets it apart. An array of colors and flake designs invite you to craft a personalized floor, making every space a canvas of self-expression. Whether in homes, showrooms, or commercial areas, this coating embodies more than protection – it's a testament to the marriage of functionality and aesthetics. Dive into a realm where floors don't just serve, they inspire, reflecting resilience and elegance in equal measure.

Features Of Epoxy Flake Floor Coating:

- 1. Fire-resistant properties enhanced safety
- 2. Multi-purpose versatile usage options
- 3. Ideal for barns and farm structures
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China