

Seamless Epoxy Multi Flake Coating Against Retail Warehouses Daily Wear

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 400KG
- Price:
- Packaging Details:
- Delivery Time:
- US\$4.0-6.0/Kg Bottle/Carton/Wooden Box

CHINA

CREKOAT

TDS, MSDS CK-FL2001

- Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Branding Descriptor:
- Central Attribute:
- Key Words:
- Materials:
- Application:
- Mixing Ratio:
- Pot Life:
- Shelf Life:
- Highlight:

- Epoxy Floor Paint Sprinkles Advanced Polymer Blend
- Interior And Exterior Use
- Epoxy With Flakes
- Wood, Ceramic Tile, Concrete
- 2:1 By Weight
- 40 Minutes
- 12 Months
- Seamless Epoxy Multi Flake Coating, Warehouses Epoxy Multi Flake Coating

CREKOAT



Our Product Introduction

Product Description

Seamless Epoxy Multi Flake Coating Against Retail Warehouses Daily Wear

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating: the convergence of resilience and aesthetics. Marrying epoxy resin with decorative flakes, it births a floor that redefines spaces. Beyond its robustness against daily wear, it offers a creative canvas. A spectrum of colors and flake patterns beckons artistic expression, making every floor a unique tapestry. From residences to retail spaces, it transforms environments into reflections of individuality. This coating isn't just utilitarian; it's a statement of elegance. Seamlessly blending durability and design, it narrates a story where strength and aesthetics coexist harmoniously.

Features Of Epoxy Flake Floor Coating:

- 1. Automotive showrooms cars attractively
- 2. Withstands gymnasium heavy equipment
- 3. Endures warehouses constant movement
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
	· · · · · · · · · · · · · · · · · · ·	
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	• • • • • • • •	
	kitchens and living rooms.	





No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China