

Superior Bonding Blue Flake Epoxy Floor Coating Blending Durability Naturally De Foaming

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Labelled Merchandising: Epoxy Flake Floor Coatings
 Characteristic Detail: Exceptional Gloss Retention
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Blue Flake Epoxy Floor Coating,

Superior Bonding Flake Epoxy Floor Coating



Product Description

Superior Bonding Blue Flake Epoxy Floor Blending Durability With Design

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating: a union of strength and sophistication. Through the fusion of epoxy resin and decorative flakes, it shapes a floor that's not only tough but also a testament to artistry. Its ability to withstand daily challenges is matched only by its visual allure. However, what truly sets it apart is its versatility as a creative medium. With an array of colors and flake designs, it enables the transformation of spaces into personal expressions. Whether it's a residence, showroom, or office, this coating brings more than functionality – it embodies elegance. Seamlessly blending durability with design, it forms an intricate dance that speaks to both resilience and aesthetics.

Features Of Epoxy Flake Floor Coating:

- 1. Food processing hygienic for production areas
- 2. Seamless integration blends flawlessly
- Strong adhesion for lasting protection
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China