

# Bulk Resilient Finish Epoxy Flake Floor Coating Customizable Thickness

## **Basic Information**

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



# **Product Specification**

Item Denotation: Decorative Flakes For Concrete Paint

Noted Attribute: Ultra-Low VOC Emissions
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Resilient Finish Epoxy Flake Floor Coating,

**Epoxy Flake Floor Coating Customizable** 

Thickness



## **Product Description**

#### Resilient Finish Epoxy Flakes Bulk Floor Coating Customizable Thickness

#### Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating harmonizes durability and design. By blending epoxy resin with decorative flakes, it constructs a floor that's not only robust but also visually captivating. Its resistance against daily wear is exceptional, but its true magic lies in its artistic potential. A palette of colors and flake patterns empowers you to curate a floor that tells a unique story. This coating transcends mere functionality, becoming an artistic statement in spaces ranging from homes to commercial areas. Seamlessly fusing strength and aesthetics, it crafts an experience where floors become more than just surfaces – they embody a symphony of endurance and elegance.

#### Features Of Epoxy Flake Floor Coating:

- 1. Withstands wear and tear effectively
- 2. Adjustable coating depth for needs
- 3. Strong adhesion for lasting protection
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

#### **Advantages Of Epoxy Flake Floor Coating:**

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

#### **Product Descriptions Of Epoxy Flake Floor Coating:**

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China