

## MSDS Epoxy Flake Floor Coating For Concrete Enhanced Safety Withstands Heavy Loads

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 400KG
- Price: US\$4.0-6.0/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



### Product Specification

- Trade Labeling Convention: Color Flake Flooring
- Key Property: Industrial-Grade Strength
- Key Words: Interior And Exterior Use
- Materials: Epoxy With Flakes
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **MSDS Epoxy Flake Floor Coating, Safety Epoxy Flake Floor Coating**



## Product Description

### Decorative Flakes For Concrete Enhanced Safety Withstands Heavy Loads

#### Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating: Where Creativity Meets Resilience. By blending epoxy resin and decorative flakes, it engineers a floor that embodies strength and showcases personal style. Its durability is undisputed, but its real magic lies in its design flexibility. A palette of colors and flake patterns invites you to paint your floor with unique character. From homes to commercial spaces, this coating becomes a testament to the fusion of function and aesthetics. It's not just about protecting surfaces; it's about creating a visual journey. The dance between toughness and design makes each step on the floor a celebration of both durability and sophistication.

#### Features Of Epoxy Flake Floor Coating:

1. Slip-resistant texture for secure footing
2. Withstands heavy loads without damage
3. Strong adhesion for lasting protection
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

#### Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

#### Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150 mPa.s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China