



Decorative Polyaspartic Flake Floor Blending Epoxy Resin With Color Chips

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 400KG
- Price: US\$4.0-6.0/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Item Signature: Full Flake Floor
- Vital Characteristic: High Clarity And Reflectivity
- Key Words: Interior And Exterior Use
- Materials: Epoxy With Flakes
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Decorative Polyaspartic Flake Floor, Polyaspartic Flake Floor Blending Epoxy Resin**



Product Description

Decorative Polyaspartic Flake Floor Blending Epoxy Resin With Color Chips

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating transforms floors into artful expressions. Blending epoxy resin with decorative flakes, it constructs a robust surface that's also a feast for the eyes. Its endurance is unquestionable, yet its true power lies in its creative versatility. A spectrum of colors and flake designs allows you to sculpt a floor that's uniquely yours. From homes to high-traffic zones, this coating seamlessly merges strength and style. It's more than protection; it's a design journey. The interplay of sturdiness and aesthetics crafts a floor that whispers sophistication with every step, reminding us that durability can be a canvas for personal identity.

Features Of Epoxy Flake Floor Coating:

1. Long-lasting vibrancy over time
2. Maintains integrity in varying climates
3. Strong adhesion for lasting protection
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150 mPa·s
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	



 +8615017402317  info@crekoat.com  epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China