

# High Gloss Flake System Epoxy Floor Coating Texture Variety Creates A Shiny Surface

## **Basic Information**

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



## **Product Specification**

Merchandise Monograph: Colour Flake Epoxy Flooring
 Standout Quality: High-Endurance Flooring
 Key Words: Interior And Exterior Use
 Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Flake System Epoxy Floor Coating, High Gloss Epoxy Floor Coating



## **Product Description**

#### High Gloss Flake System Epoxy Texture Variety Creates A Shiny Surface

#### Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating is the fusion of resilience and artistry. Marrying epoxy resin with decorative flakes, it crafts a floor that stands strong while making a visual statement. Beyond its durability, it's a playground of creative possibilities. A palette of colors and flake patterns lets you design a floor that's uniquely yours. From residential spaces to commercial settings, this coating doesn't just cover surfaces; it transforms them into personalized canvases. It's more than protection; it's the embodiment of style. The interplay of robustness and aesthetics creates a floor that silently speaks of strength and elegance, making every step taken a testament to the balance between form and function.

### Features Of Epoxy Flake Floor Coating:

- 1. Creates a shiny and elegant surface
- 2. Diverse tactile options for preference
- 3. Strong adhesion for lasting protection
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

#### **Advantages Of Epoxy Flake Floor Coating:**

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

#### **Product Descriptions Of Epoxy Flake Floor Coating:**

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China