

Low Maintenance Garage Floor Flake Epoxy Anti Abrasion Non - Toxic

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 400KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Article Distinction: Stone Coat Countertops Mica Flakes

 Distinguishing Self-Healing Properties AspectQuality:

Key Words: Interior And Exterior UseMaterials: Epoxy With Flakes

• Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: Garage Floor Flake Epoxy Anti Abrasion,

Non Toxic Garage Floor Flake Epoxy

CREKOAT



Product Description

Low Maintenance Garage Floor Flake Epoxy Anti-Abrasion Non-Toxic

Quick Details Of Epoxy Flake Floor Coating:

Epoxy Flake Floor Coating redefines flooring aesthetics and functionality. Blending epoxy resin with decorative flakes, it forges a floor that's not only durable but also a masterpiece of design. Its ability to withstand daily wear is unparalleled, yet its true charm lies in its artistic potential. A vibrant spectrum of colors and flake patterns empowers you to create a floor that's a reflection of your taste. From homes to commercial spaces, this coating elevates surfaces to art. It's more than just a floor covering; it's a canvas where durability meets expression. The blend of sturdiness and aesthetics transforms each footstep into a dance between strength and elegance.

Features Of Epoxy Flake Floor Coating:

- 1. Minimal care required for longevity
- 2. Resists surface damage from friction
- 3. Strong adhesion for lasting protection
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China