

Scratch Resistant Clear Epoxy Resin Coating And Casting Resin **Exceptionally Tough TDS**

Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-ART1001 Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Bottle/Carton/Wooden Box Packaging Details:

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

. Supply Ability: 1000000 Ton/Year



Product Specification

. Trade Nameplate: Clear Flexible Epoxy

Dominant Factor: **Eco-Friendly**

Key Words: Pouring Clear Epoxy 2 Part Clear Resin Materials: Casting, Coating And Art · Application:

Mixing Ratio: 1:1 By Volume Pot Life: 40 Minutes Shelf Life: 12 Months

• Highlight: Scratch Resistant Clear Epoxy Resin,

TDS Clear Epoxy Resin

CREKOAT



Product Description

Scratch-Resistant Coating And Casting Resin Exceptionally Tough

Quick Details Of Clear Epoxy Resin:

Clear Epoxy Resin is a versatile material known for its self-leveling properties and transparent finish. It's used in various applications, such as crafting, woodworking, and jewelry making, where its ability to encapsulate objects adds depth and creativity to projects. Its resistance to yellowing and UV damage ensures long-lasting clarity. Whether you're a professional artist or a DIY enthusiast, Clear Epoxy Resin offers a durable and visually appealing solution for your creative endeavors.

Features Of Clear Epoxy Resin:

- 1. Exceptionally tough and scratch-resistant
- 2. Perfect for encapsulating cherished mementos
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	1800-2200 mPa·s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China