

VOC Free Ultra Clear Casting Resin Yields Flawless Glass Like Surface

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-ART1001
Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 1000000 Ton/Year



Product Specification

• Designated Merchandising: Transparent Epoxy Glue

• Defining Hallmark: High Build

Key Words: Pouring Clear Epoxy
 Materials: 2 Part Clear Resin
 Application: Casting, Coating And Art

Mixing Ratio: 1:1 By VolumePot Life: 40 MinutesShelf Life: 12 Months

Highlight: Ultra Clear Casting Resin,
 VOC Free Clear Casting Resin

CREKOAT



Product Description

VOC Free Ultra Clear Casting Resin Yields A Flawless Glass-Like Surface

Quick Details Of Clear Epoxy Resin:

Clear Epoxy Resin's versatility extends to various applications. Its thermal insulation properties make it ideal for creating coffee tables with embedded LED lights. Artists utilize it for custom circuit boards and artworks with LED displays. Its adhesive qualities are valuable in architectural models and industrial coatings. Whether in art, electronics, or industry, Clear Epoxy Resin empowers innovation and ensures enduring, high-quality results. Clear Epoxy Resin's ability to resist water and chemicals extends its use in constructing chemical-resistant laboratory equipment and creating robust industrial coatings. Whether in art, electronics, or industrial settings, this resin empowers innovation and ensures enduring, high-quality results.

Features Of Clear Epoxy Resin:

- 1. Yields a flawless, glass-like surface
- 2. Resists water damage and chemical exposure
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	1800-2200 mPa·s	600-800 mPa·s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China