

Eco - Friendly Pouring 2 Part Casting Resin Achieves Pristine Glass Like **Surface**

Basic Information

. Place of Origin: **CHINA** . Brand Name: **CREKOAT** TDS, MSDS · Certification: Model Number: CK-ART1001 Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Bottle/Carton/Wooden Box Packaging Details:

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

. Supply Ability: 1000000 Ton/Year



Product Specification

• Brand Representation: Clear Epoxy For Wood Table

Trait: **Excellent Adhesive** Pouring Clear Epoxy . Key Words: 2 Part Clear Resin Materials: Casting, Coating And Art · Application:

Mixing Ratio: 1:1 By Volume Pot Life: 40 Minutes Shelf Life: 12 Months

• Highlight: Eco Friendly 2 Part Casting Resin, **Pouring 2 Part Casting Resin**

CREKOAT



Product Description

Eco-Friendly 2 Part Casting Resin Achieves A Pristine Glass-Like Surface

Quick Details Of Clear Epoxy Resin:

Clear Epoxy Resin's versatility extends to unique applications. Its exceptional scratch resistance makes it ideal for creating durable, glossy epoxy countertops and tabletops that maintain their pristine appearance even in high-traffic areas. Artists appreciate its compatibility with alcohol inks, allowing for the creation of vivid, fluid resin art pieces with stunning abstract designs. Its low VOC content and eco-friendly formulations make it a responsible choice for crafting sustainable furniture and decor that promotes environmental consciousness. Whether in interior design, art, or eco-conscious living, this resin empowers creativity while prioritizing durability and sustainability.

Features Of Clear Epoxy Resin:

- 1. Achieves a pristine, glass-like surface
- 2. Shields against moisture and chemicals
- 3. Free of solvents, VOC/BPA free
- 4. Highest UV protection, anti yellowing
- 5. Durable, water-clear, high-gloss finish
- 6. Useable on wood, concrete, glass

Advantages Of Clear Epoxy Resin:

CK-ART1001 A High Viscosity Epoxy Resin, designed for coating and creative applications. An easy to measure 1:1 ratio self-leveling product, with excellent air release properties, is UV Stable, low in VOC's and in odour. This product has been designed to add a diamond-like finish to your resin art, acrylic pours, mosaics, photographs, prints, timber surfaces, sculptures, and more. Can be applied by pouring, brushing on, or with a roller to substrates such as Art Boards, MDF, acrylic sheet, concrete, metal, wood and more.

Product Descriptions Of Clear Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	1800-2200 mPa·s	600-800 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by volume	
Hardness	Shore, D85-90	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Max Pour Depth	1-8cm max per single pour	
Shelf Life	12 Months	
Application	Ideal for all Casting, Coating and Art Projects including Cutting Boards,	
	Coasters, Countertops, Bartop, Resin Art, Resin Jewelry, Coating Artwork and	
	Acrylic Pour Paintings, Geode Paintings, Molds, River Tables	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China