

One Coat Epoxy Flake Floor Biodegradable Variants Environmentally Friendly

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Item Label: Flake Floor CoatingsPeculiarity: Seamless Bond

Key Words: Interior And Exterior UseMaterials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: One Coat Epoxy Flake Floor,

 ${\bf Biodegradable\ Epoxy\ Flake\ Floor},$

Flake Floor Coatings Environmentally Friendly



Product Description

One-Coat Application Epoxy Flake Floor Biodegradable Variants Environmentally Friendly

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coating seamlessly combines durability with artistic expression. It withstands heavy traffic and daily wear, ensuring long-lasting value. Its resistance to chemicals makes it ideal for spill-prone areas. What truly distinguishes it is the creative canvas it offers, with a wide spectrum of colors and flake patterns that transform spaces into unique expressions of personal style. Maintenance is simple with its easy-to-clean, seamless surface. Versatile and suitable for various settings, from residential garages to commercial spaces, it provides both resilience and aesthetics, with slip-resistant properties enhancing safety. Epoxy flake floor coating isn't just a floor; it's a statement of durability and artistry.

Features Of Epoxy Flake Floor Coating:

- 1. Environmentally friendly options available
- 2. Efficient single-layer installation
- 3. Strong adhesion for lasting protection
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	
	Nitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China