

Chemical Vapor Resistance Epoxy Flake Floor Coating Resists Airborne Exposure

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

 Labelled Commodity E Designation:

Epoxy Paint Chip Floor

Prominent Marker: Excellent Flow

Key Words: Self-Leveling, Fast Curing

Materials: Epoxy With Flakes

• Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: Vapor Resistance Epoxy Flake Floor Coating,

Epoxy Flake Floor Coating Resists Airborne



Product Description

Chemical Vapor Resistance Epoxy Flake Floor Coating Resists Airborne Exposure

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coating is the fusion of strength and artistry. While it excels in durability, capable of withstanding high traffic and chemicals, its true allure lies in the realm of creativity. A wide spectrum of colors and flake patterns empowers individualized, artistic floor designs. Whether in garages, homes, or commercial spaces, it transcends utility to make a style statement. Maintenance is a breeze due to its easy-to-clean seamless surface. Slip-resistant features enhance safety, while the impermeable finish wards off moisture. Epoxy flake floor coating isn't merely about covering floors; it's about transforming them into canvases where every step celebrates both resilience and elegance, ushering in a new era where durability and personal expression coexist harmoniously.

Features Of Epoxy Flake Floor Coating:

- 1. Resists airborne chemical exposure
- 2. Adds minimal weight and thickness
- 3. Strong adhesion for lasting protection
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China