

Smooth Textured Variations Epoxy Flake Floor Coating Moisture Proof For Different Surfaces

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Trade Marked Title: Decorative Flakes For Garage Floors

Notable Element: Moisture-Proof

Key Words: Self-Leveling, Fast Curing

Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Smooth Textured Epoxy Flake Floor Coating,

Epoxy Flake Floor Coating Moisture Proof



Product Description

Smooth Textured Variations Epoxy Flake Floor Coating For Different Surfaces

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coating redefines flooring by blending strength with creativity. Beyond its impressive durability, capable of withstanding heavy traffic and chemical exposure, it unveils endless design possibilities. A rich palette of colors and flake patterns empowers personalized floor creations. Whether in garages, homes, or commercial spaces, it goes beyond the practical, becoming an artistic medium. Maintenance is a breeze, with its easy-to-clean, seamless surface. Slip-resistant features boost safety, while its impermeable finish keeps moisture at bay. Epoxy flake floor coating doesn't merely protect floors; it transforms them into canvases where each step celebrates both resilience and style. It heralds an era where durability and individual expression unite seamlessly.

Features Of Epoxy Flake Floor Coating:

- 1. For sensitive electronic areas
- 2. Offers choices for different surfaces
- 3. Strong adhesion for lasting protection
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China